



# LUXAPOOL Luxury Coatings - for pools, and aquatic surfaces.

LUXAPOOL Coatings are available in two distinct product formulations which are designed for different uses — Epoxy & Chlorinated Rubber

**LUXAPOOL (2-PACK) EPOXY COATINGS** are excellent for all new swimming pool applications and can also be used to give a beautiful luxury finish to older pools. **LUXAPOOL** Epoxy Coatings are also well suited to application over old and new cement render, fibreglass, marblesheen and also previously painted epoxys. **LUXAPOOL** Epoxy Coatings provide a smooth, hard surface which is easy to maintain. All **LUXAPOOL** Epoxy Coatings feature a durable luxury finish with improved resistance to chalking and the effects of salt-water and chlorinated chemicals. They are algae controlled and safe for use with fish and mammals.



**LUXAPOOL CHLORINATED RUBBER COATINGS** are formulated for use over old or new concrete based swimming pools. They are especially formulated to resist the destructive effects of swimming pool chemicals and have a proven record of longevity and durability. They are especially formulated to resist the destructive effects of swimming pool chemicals and have a proven record of longevity and durability. **LUXAPOOL** Chlorinated Rubber Coatings feature fine sealing properties and a hard satin finish which is also easy to maintain with very good resistance to salt-water and chlorinated chemicals. They are algae controlled and can be easily re-coated when desired.

## COLOUR RANGE

REGENCY WHITE	RIVERSAND	DESERT GOLD (C)	FERN GREEN
RAINFORREST	SPRING APPLE (C)	EMERALD GREEN (C)	POND GREEN
WHITE (C)	BROOK GREEN (C)	AQUA MIST (C)	ATLANTIS *
JACARANDA	CRESTWOOD (C)	PACIFIC BLUE (C)	ADRIATIC
TAHITIAN	MISTY BLUE	MID BLUE (C)	DEVONPORT *
SERENITY	TEMPEST GREY	PLATINUM BLUE	SLATE * (C)
			BLACK (C)

(C) Also available in Chlorinated Rubber  
Over 200 Australian Standard (AS) and Designer colours available on request. Premium charges and lead times apply.  
\*Stock Designer Colours - premium charges apply.  
Disclaimer: The samples in this colour card are as near to the actual colours as the printing process permits. Actual colours vary from this colour card and from batch to batch. Prospective users must satisfy themselves as to the suitability of the coating and colour prior to application. Charges may apply for colour samples.

### LUXAPOOL EPOXY COATINGS (2-pack kit)

**COVERAGE**  
Approximately 20m<sup>2</sup>/pack for 2coats. 14m<sup>2</sup>/pack for 3 coat system. Apply a minimum of two coats of **LUXAPOOL** Epoxy Coating. An average pool (10m x 5m x 1.5m deep) requires approximately 7 x 3.5L kits per two (2) coat finish.

**APPLICATION**  
Apply by brush and roller only over a properly prepared substrate. Refer to the relevant Application Guide for each substrate type prior to application.

**CLEAN-UP**  
Clean all equipment with **LUXAPOOL** Solvent LT.

**COLOURS**  
**LUXAPOOL** Epoxy Coatings are available in 22 standard and 3 stock Designer colours. Over 200 Australian Standard and other Designer colours available by special arrangement.

### LUXAPOOL CHLORINATED RUBBER

**COVERAGE** Approximately 5 - 8m<sup>2</sup> per L depending on surface type and porosity.

**THINNING** Thinning is not recommended.

**APPLICATION** By brush, roller or spray. Avoid heavy coats which may cause blistering. NEVER APPLY OVER DAMP SURFACES. Exercise caution when applying in very hot and/or sunny conditions as this makes application difficult and may cause blistering. Use of a shade cloth may be beneficial. Apply a minimum of 3 to 4 coats for best results. Refer to the relevant Application Guide for each substrate type prior to application.

**CLEAN-UP** Clean all equipment with Chlorinated Rubber Solvent (CRS).

**COLOURS** **LUXAPOOL** Chlorinated Rubber Coatings are available in 11 standard colours.

### MAINTENANCE

Make sure to let your pool shop know that your pool has either an Epoxy or Chlorinated Rubber coating and our recommended pool chemistry.

### POOL CHEMISTRY

- **MAINTAIN pH** between 7.6 and 7.8 • **ALKALINITY** at a minimum of 140-160, between 160 - 180 ppm for dark colours
- **CALCIUM HARDNESS** of 250 ppm - 300 ppm or more
- Keep **CHLORINE LEVELS** at a minimum (<3.0) consistent with good hygiene
- **MINIMISE USE OF ACID** where possible • **Brushing down your pool every 4 - 6 weeks will maintain a coating of good integrity and improve longevity.**

The application data above is a general reference guide only. Application Guides specific to your pool surface can be obtained from Colormaker Industries or your authorised **LUXAPOOL** stockist.  
PLEASE NOTE — all pools vary in respect to surface type, texture, and soundness. Also climatic conditions prior to, during and after the application of **LUXAPOOL** Coatings affect the finished coating. These variables must be taken into account by the user and are beyond the control of Colormaker Industries, therefore Colormaker Industries cannot accept responsibility for imperfections such as chalking, discolouration, blistering, flaking or peeling.



PO Box 462, Brookvale NSW 2100, Australia • Phone: +61 2 9939 7977  
Fax: +61 2 9939 6685 • email: sales@luxapool.com.au  
www.luxapool.com.au

#### LUXAPOOL DISTRIBUTORS

VIC: Phone (03) 9720-8777 dpjadmin@bigpond.com.au QLD: Phone (07) 3807-2454 cctech@bigpond.com  
SA & NT: Phone (08) 8234-8330 huntadmin@huntdist.com.au ACT: Phone (02) 6280-6476 hydroquip@ozemail.com.au  
WA: & NT: Phone (08) 9385-2277 or fax: (08) 9284-2274 TAS: Phone (03) 6234-5800 info@poolquip.com.au  
wa.pool.pride@colormaker.com.au NZ: Phone +64 9 444-6808 pooldoctor@xtra.co.nz

Available from: [www.DirectPoolSupplies.com.au](http://www.DirectPoolSupplies.com.au)  
Ph: 1800 648 363